

## // BULK MATERIAL



### // 704HA HD

#### Suction excavator 10 bar (150 psi) - Corrugated

**Tube:** red NR - abrasion resistant.

**Reinforcement:** high tensile textile cords with embedded steel helix wire - antistatic wire.

**Cover:** black conductive SBR/NR - abrasion and ozone resistant.

**Application:** bulk material suction and delivery in heavy duty applications.

Specially designed for suction excavators.

Corrugated construction for maximum flexibility.

**Constant operation:** -40 °C +80 °C (-40 °F +176 °F)

Art. number	ID	OD	WP	BP	BR	Vacuum	Weight	Length	Special feature
	(mm)	(mm)	(bar)	(bar)	(mm)	%	(kg/m)	(m)	
2017195	254,0	297,0	10	30	1,016	100	24,610	6,900	<b>Enlarged ends</b> ID 264mm max OD 293mm length 120mm
2017189	254,0	297,0	10	30	1,016	100	24,610	5,300	<b>Soft ends</b> length 70mm max OD 293mm
2017190	254,0	297,0	10	30	1,016	100	24,610	6,900	<b>Soft ends</b> length 70mm max OD 293mm
2017191	254,0	297,0	10	30	1,016	100	24,610	7,900	<b>Soft ends</b> length 70mm max OD 293mm