




BREWERY HOSES



// 422LH



Alcoholic beverages S&D 10 bar (150 psi)

Tube: white chlorobutyl.

Reinforcement: high tensile textile cords with embedded helix wires.

Cover: red NR/EPDM – abrasion and ozone resistant.

Application: liquid food and alcoholic beverages suction and delivery max 95% proof. Sterilize with 130 °C (266 °F) steam for 30 minutes or with 5% soda solution.

Temperature: -30 °C +108 °C (-22 °F +226 °F)

Art. number	ID	ID	OD	WP	BP	BR	Vacuum	Weight	Length
	(mm)	(in)	(mm)	(bar)	(bar)	(mm)	%	(kg/m)	(m)
2016598	38	1 1/2"	52	10	30	76	100	1,00	30,5
2016600	51	2"	65	10	30	102	100	1,31	30,5
2014699	63	2 1/2"	79	10	30	127	100	2,37	30,5

// 45BLI DH BREWER



Alcoholic beverages D 10 bar (150 psi)

Tube: white chlorobutyl.

Reinforcement: high tensile textile cords.

Cover: orange EPDM – abrasion and ozone resistant.

Application: liquid food and alcoholic beverages delivery max 95% proof. Sterilize with 110 °C (266 °F) steam for 30 minutes or with 5% soda solution.

Temperature: -30 °C +120 °C (-22 °F +248 °F)

Art. number	ID	ID	OD	WP	BP	Weight	Length
	(mm)	(in)	(mm)	(bar)	(bar)	(kg/m)	(m)
2017601	25	1"	37	10	30	1,00	40
2017533	32	1 1/4"	48	10	30	1,29	40
2017539	38	1 1/2"	56	10	30	1,86	40
2017602	51	2"	71	10	30	2,58	40
2017603	63	2 1/2"	85	10	30	3,15	40

Branded:  **DUNLOPHIFLEX** BREWER 45BLI - BIIR - CE 1935/2004 - 

// I389S200

SMS 1145

Female - Serrated hose shank with collar - Stainless steel 316



Art. number	ID (in)	Hose ID (mm)	Thread type	Thread (in)
2301612	1"	25,0	SMS	40 x 1/6"
2308650	1 1/4"	32,0	SMS	48 x 1/6"
2301813	1 1/2"	38,0	SMS	60 x 1/6"
2301276	2"	51,0	SMS	70 x 1/6"
2301637	2 1/2"	63,0	SMS	85 x 1/6"
2301814	3"	76,0	SMS	98 x 1/6"
2302568	4"	102,0	SMS	132 x 1/6"

// I389S100

SMS 1145

Male - Serrated hose shank with collar - complete with seal -
Stainless steel 316



Art. number	ID (in)	Hose ID (mm)	Thread type	Thread (in)
2301812	1 1/2"	38,0	SMS	60 x 1/6"
2301611	2"	51,0	SMS	70 x 1/6"
2301638	2 1/2"	63,0	SMS	85 x 1/6"
2301737	3"	76,0	SMS	98 x 1/6"

// I389Q200

DIN 11851

Female with round nut - Serrated hose shank -
Stainless steel 316



Art. number	ID (in)	Hose ID (mm)	Thread (in)
2301816	1"	25,0	52 x 1/6"
2302565	1 1/4"	32,0	58 x 1/6"
2301741	1 1/2"	38,0	65 x 1/6"
2301639	2"	51,0	78 x 1/6"
2301640	2 1/2"	63,0	95 x 1/6"
2301641	3"	76,0	110 x 1/4"
2302566	4"	102,0	130 x 1/4"

// I389Q100

DIN 11851

Male - Serrated hose shank complete with seal -
Stainless steel 316



Art. number	ID (in)	Hose ID (mm)	Thread type	Thread (in)
2302561	1"	25,0	DIN11851	52 x 1/6"
2302562	1 1/4"	32,0	DIN11851	58 x 1/6"
2302563	1 1/2"	38,0	DIN11851	65 x 1/6"
2301713	2"	51,0	DIN11851	78 x 1/6"
2301642	2 1/2"	63,0	DIN11851	95 x 1/6"
2301643	3"	76,0	DIN11851	110 x 1/4"

// I307U-RK

I307U-RK

Serrated ferrule - Stainless steel 316



Art. number	ID (in)	Hose ID (mm)	Hose OD Range (mm)
2307446	1/2"	13,0	19 - 21
2306863	3/4"	19,0	28 - 32
2307442	1"	25,0	35 - 40
2307447	1 1/4"	32,0	41 - 44
2307845	1 1/2"	38,0	52 - 57
2303961	1 1/2"	38,0	49 - 53
2307448	2"	51,0	60 - 64
2303962	2"	51,0	64 - 67
2304503	2 1/2"	63,0	79 - 82
2303964	2 1/2"	63,0	87 - 91
2304504	3"	76,0	88,5 - 92,5
2303965	3"	76,0	95 - 101
2304556	4"	102,0	117 - 122



// DUNLOP HIFLEX SCANDINAVIA

// SWEDEN

HEADQUARTER

DUNLOP HIFLEX AB

Seldonsvägen 2, Halmstad
+46 (0)10-414 44 00

info@dunlophiflex.se

BORLÄNGE

+46 (0)10-414 46 00

borlange@dunlophiflex.se

GÖTEBORG

+46 (0)10-414 45 40

goteborg@dunlophiflex.se

HALMSTAD

+46 (0)10-414 44 04

halmstad@dunlophiflex.se

HELSINGBORG

+46 (0)10-414 45 60

helsingborg@dunlophiflex.se

LJUNGBY

+46 (0)10-414 45 20

ljungby@dunlophiflex.se

MALMÖ

+46 (0)10-414 45 00

malmo@dunlophiflex.se

NORRKÖPING

+46 (0)10-414 45 70

norrkoping@dunlophiflex.se

STOCKHOLM

+46 (0)10-414 45 80

stockholm@dunlophiflex.se

UMEÅ

+46 (0)10-414 45 30

umea@dunlophiflex.se

VÄXJÖ

+46 (0)10-414 45 10

vaxjo@dunlophiflex.se

ÖREBRO

+46 (0)10-414 45 50

orebro@dunlophiflex.se

// NORWAY

HEADQUARTER

DUNLOP HIFLEX AS

Jogstadveien 39, Kjeller
+47 23 00 47 00

sales@dunlophiflex.no

BERGEN

+47 23 00 47 70

bergen@dunlophiflex.no

HARSTAD

+47 23 00 48 10

harstad@dunlophiflex.no

KJELLER/OSLO

+47 23 00 47 00

oslo@dunlophiflex.no

KRISTIANSAND

+47 23 00 47 50

kristiansand@dunlophiflex.no

SARPSBORG

+47 23 00 48 30

sarpsborg@dunlophiflex.no

STAVANGER

+47 23 00 47 60

stavanger@dunlophiflex.no

TROMSØ

+47 23 00 48 20

tromso@dunlophiflex.no

TRONDHEIM

+47 23 00 48 00

trondheim@dunlophiflex.no

ÅLESUND

+47 23 00 47 80

alesund@dunlophiflex.no

// DENMARK


HEADQUARTER

DUNLOP HIFLEX A/S

Kokholm 5, Kolding
+45 43 25 40 00

kundeservice@dunlophiflex.dk





HEAD OFFICE DUNLOP HIFLEX SCANDINAVIA

Dunlop Hiflex AB

Seldonsvägen 2, 302 62 Halmstad - Sweden

Tel +46 (0)104-14 44 00

info@dunlophiflex.se

www.dunlophiflex.se