

RTD[®] LIQUID

Hand Applied Metal Cutting Lubricant

RTD[®] Liquid is a viscous fluid containing extreme pressure additives for use in reaming, tapping, drilling and other metal cutting operations. RTD[®] is suitable for all metals including hardened steels, titaniums and nimonics. This product significantly reduces friction giving superb cutting performance.

RTD[®] Liquid can also be added to ordinary mineral cutting oil for the most severe cutting operations, such as broaching and gear cutting on the toughest metals.

Features

- Ultimate cutting performance
- Flows to cutting edge
- Oil and solvent free
- Suitable for automatic application on CNC machines
- Contains no silicones

Directions for Use

RTD[®] Liquid is applied straight to the cutting operation, it is also available in a handy squeeze bottle for ease of use.

When used as a mineral cutting oil reinforcement, add between 1 and 5 parts of RTD[®] Liquid to 100 parts of neat mineral cutting oil.

Appearance	Brown liquid
Odour	Mild pine
Shell 4-Ball	
Weld Load (Neat)	>800 kg
Weld Load (5% in Oil)	315 kg
Solvents	None
Storage	Store at normal ambient temperature (5 to 30°C)
Pack Sizes – Part Codes	400g - 53072 5 ltr - 53076 20 ltr - 53078 200 ltr - 53079

Date: Jan-09

T +44 (0) 113 232 2600

F +44 (0) 113 232 2740

E customer-service@rocol.com

www.rocol.com

ROCOL House, Swillington, Leeds LS26 8BS

Registered Company No. 559693 VAT No. 742 0531 67

Registered Office: Admiral House, St Leonard's Road, Windsor, Berkshire SL4 3BL

ROCOL A division of *ITW* Ltd



BS EN ISO 9001
Certificate No. FM 12448



BS EN ISO 14001
Certificate No. EMS 67596



OHSAS 18001
Certificate No. OHS 78173



INVESTOR IN PEOPLE

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.