

 **ALFAGOMMA**

## SHIPBUILDING & MILITARY



## Standards & Regulations

			
3-A Sanitary Standards Inc.	Decreto Ministeriale	Europen Commission	Energy Institute
			
European Norms	Food and Drug Administration	International Organization for Standardization	Marine Equipment Directive
			
Society of Automotive Engineers	U.S. Department of Defence	U.S. Coast Guard – SAE J1942	

## Approvals & Certificates

			
American Bureau of Shipping	American Petroleum Institute	Bundesamt für Ausrüstung, Informationstechnik und Nutzung der Bundeswehr	Bureau Veritas
			
Japanese Ship Classification Society	China Classification Society	Chinese Mining	Det Norske Veritas
			
Dreal	Korean Register	Lloyd's Register	Registro Italiano Navale
			
United States Department of Transportation	U.S. Mine Safety and Health Administration		



---

Since 1956 Alfagomma has been manufacturing and delivering top quality products all over the world.

Alfagomma believe in the importance of offering an excellent service to all its customers along with a continuous new product research and development, a constant high quality exceeding ISO 9001 quality standards and full compliance with ISO 14001 environmental norms, as well as a constantly upgrading range of Type Approvals.

### **ALFAGOMMA GROUP**


---



**ALFAGOMMA** // **DUNLOPHIFLEX** // **HIFLEX** // **ARGUS**



## OUR EXPERIENCE ON BOARD



## // DOGLEG

Alfagomma Dogleg is an innovative and easy to install shock and vibration dampener hose assembly for naval vessels.

Alfagomma Dogleg provides the required flexibility to **absorb movement in multiple directions** and guarantees long service life and **advanced performances** in the severe marine environment.

Compared to current solutions available on the market, Dogleg assemblies are **easier to install and replace directly on-board by non-specialised field technicians**, thus reducing costs and lengthy downtimes.

The solution meets the strict standards required by military navies and shipbuilding companies for new naval units and refits.



### AN INNOVATIVE SOLUTION

- **SINGLE SOURCE INTEGRATED SYSTEM SUPPLIER**
- **IN-HOUSE MANUFACTURING**
- ASSEMBLING AND TESTING (**ISO 9001-14001**)
- **RINA TYPE APPROVAL** FOR MARINE REQUIREMENTS (TAC)
- EUROPEAN **MARINE EQUIPMENT DIRECTIVE** (MED)
- **MIL-STD-167** (VIBRATION) AND **MIL-S-901** (SHOCK)
- NO NEED OF HIGH-SKILLED TECHNICIANS

# // THUNDER-LOCK

**Thunder-lock is a revolutionary weldless connection for rigid pipes**, providing the same reliability as welding without the associated risks and costs.

The tube is **permanently formed and sealed** to the end configuration, through a **cold connection**, and operated using a **compact-size portable tool**, that doesn't require **any specialized technical personnel** to run. In addition to a reduction in costs and ease of use, the system guarantees a **high degree of safety**: incorporating leakage-free pipelines, no release of fumes and toxic gases, requiring no post-welding treatments; these being just some of the benefits this system provides.

Thunder-lock makes possible the **easily and fast connection of pipelines**, even in confined spaces, such as those found on board ships, representing the **best alternative to welding** and in compliance with the stringent requirements requested in both the **naval and military fields**.

## A REVOLUTIONARY CONNECTION SYSTEM

### FAST & SAFE

- COMPLETED IN 15 TO 20 SECONDS
- EASY ON-SITE INSTALLATION
- NO NEED FOR HIGHLY SKILLED TECHNICIANS
- NO NEED FOR FIRE-FIGHTING SUPERVISION
- DESIGNED WITH SAFETY BACKUP O-RING
- HIGH RATING PRESSURES

### CLEAN & SMART

- COLD CONNECTION
- NO NEED FOR FLUSHING
- GREEN TECHNOLOGY
- FOR METRIC TUBES AND NPS PIPES
- LARGE RANGE OF CONFIGURATIONS
- WIDE VARIETY OF MATERIALS



## // RUBBER EXPANSION JOINTS

Alfagomma AG Joint range includes **highly engineered rubber expansion joints**, designed to safely absorb all directional movements, and relieve stress in the pipeline systems.

The excellence of AG Joint products is the result of a **high-performance modelling software**, an extremely **innovative robotic technology** and **top-quality raw material combination**.

The cutting-edge industrial science, applied to the design and manufacturing process, provides a **cost-effective solution** that can be tailor-made to **customer's needs**.

Prototyping trials are conducted with minimal material waste and risk of errors, thanks to an advanced high-tech system, completely removing the associated costs that traditional prototyping trials command. The process involves **FEA analysis** and **manufacturing using virtual simulation**, prior to physical production, while robotics technology ensures **accuracy and reliability** of the final products, **according to the requirements set**.

### ADVANCED MANUFACTURING TECHNOLOGY

- CUSTOMIZED PRODUCTS
- CO-ENGINEERED PROJECTS
- LARGE-SCALE OR SINGLE PARTS PRODUCTION
- SUITABLE FOR NUMEROUS APPLICATIONS
- HIGH REPEATABILITY WITHOUT ERRORS
- FEA ANALYSIS AND VIRTUAL SIMULATION
- ROBOTICS MANUFACTURING
- COST-EFFECTIVE SOLUTION



# // HYDRAULIC HOSE

DESCRIPTION	APPLICATION & FLUID COMPATIBILITY	STANDARDS & REGULATIONS	APPROVALS & CERTIFICATES
-------------	-----------------------------------	-------------------------	--------------------------

## // WIRED BRAID

 <p><b>// FLEXOPAK 1SC</b> High pressure hydraulic lines. One high tensile steel braid.</p>	<ul style="list-style-type: none"> <li><b>Petroleum based</b> -40 °C +100 °C (-40 °F +212 °F)</li> <li><b>Water based hydraulic fluids</b> -40 °C +70 °C (-40 °F +158 °F)</li> <li><b>Water and air</b> 0 °C +70 °C (32 °F +158 °F)</li> </ul>	<ul style="list-style-type: none"> <li>EN 857 1SC</li> <li>ISO 11237</li> <li>MED 2014/90/EU</li> </ul>	  
 <p><b>// AT3K - MT</b> High pressure hydraulic lines. One high tensile steel braid. Minetuff cover.</p>	<ul style="list-style-type: none"> <li><b>Petroleum based</b> -40 °C +100 °C (-40 °F +212 °F)</li> <li><b>Water based hydraulic fluids</b> -40 °C +70 °C (-40 °F +158 °F)</li> <li><b>Water and air</b> 0 °C +70 °C (32 °F +158 °F)</li> </ul>	<ul style="list-style-type: none"> <li>EN 857 1SC ø 1/4", 5/16", 3/8"</li> <li>ISO 11237</li> <li>Alfagomma proprietary hose</li> </ul>	 
 <p><b>// FLEXOR 1SN/R1AT - MT</b> High pressure hydraulic lines. One high tensile steel braid. Minetuff cover.</p>	<ul style="list-style-type: none"> <li><b>Petroleum based</b> -40 °C +100 °C (-40 °F +212 °F)</li> <li><b>Water based hydraulic fluids</b> -40 °C +70 °C (-40 °F +158 °F)</li> <li><b>Water and air</b> 0 °C +70 °C (32 °F +158 °F)</li> <li><b>CO<sub>2</sub> systems just hose assemblies with AD1 couplings up to size 1"</b></li> </ul>	<ul style="list-style-type: none"> <li>SAE 100 R1AT</li> <li>EN 853 1SN</li> <li>MED 2014/90/EU</li> <li>SAE J1942</li> </ul>	      
 <p><b>// FLEXOR 5</b> Medium pressure hydraulic lines. One high tensile steel braid.</p>	<ul style="list-style-type: none"> <li><b>Petroleum based</b> -40 °C +100 °C (-40 °F +212 °F)</li> <li><b>Water based hydraulic fluids</b> -40 °C +70 °C (-40 °F +158 °F)</li> <li><b>Water and air</b> 0 °C +70 °C (32 °F +158 °F)</li> </ul>	<ul style="list-style-type: none"> <li>SAE 100 R5</li> </ul>	
 <p><b>// FLEXOPAK 2 - MT</b> High pressure hydraulic lines. Two high tensile steel braids. Minetuff cover.</p>	<ul style="list-style-type: none"> <li><b>Petroleum based</b> -40 °C +100 °C (-40 °F +212 °F)</li> <li><b>Water based hydraulic fluids</b> -40 °C +70 °C (-40 °F +158 °F)</li> <li><b>Water and air</b> 0 °C +70 °C (32 °F +158 °F)</li> </ul>	<ul style="list-style-type: none"> <li>SAE 100 R16</li> <li>EN 857 2SC</li> <li>ISO 11237</li> <li>MED 2014/90/EU</li> <li>SAE J1942</li> </ul>	       
 <p><b>// FLEXOR 2SN/R2AT - MT</b> High pressure hydraulic lines. Two high tensile steel braids. Minetuff cover.</p>	<ul style="list-style-type: none"> <li><b>Hydraulic fluid having a flash point higher than 150 °C (302 °F) (closed cup test)</b></li> <li><b>Air and compressed air</b></li> <li><b>Sea and fresh water</b></li> <li><b>CO<sub>2</sub> fire extinguishing systems</b></li> <li><b>Sanitary systems</b></li> </ul>	<ul style="list-style-type: none"> <li>SAE 100 R2AT</li> <li>EN 853 2SN</li> <li>MED 2014/90/EU</li> <li>SAE J1942</li> </ul>	       

DESCRIPTION	APPLICATION & FLUID COMPATIBILITY	STANDARDS & REGULATIONS	APPROVALS & CERTIFICATES
 <b>// ALFAFOREST</b> High pressure hydraulic lines. Three high tensile steel braids.	<ul style="list-style-type: none"> <li><b>Petroleum based</b> -40 °C +100 °C (-40 °F +212 °F)</li> <li><b>Water based hydraulic fluids</b> -40 °C +70 °C (-40 °F +158 °F)</li> <li><b>Water and air</b> 0 °C +70 °C (32 °F +158 °F)</li> </ul>	<ul style="list-style-type: none"> <li><b>MED 2014/90/EU</b></li> <li><b>Alfagomma proprietary hose</b></li> </ul>	  
<b>// WIRED SPIRAL NEW</b>			  
 <b>// 5K STEEL ARMOUR API 16D</b> API Spec 16D Flame resistance. Two high tensile steel braids or four/six high tensile steel spirals.	<ul style="list-style-type: none"> <li><b>Petroleum based</b> -40 °C +100 °C (-40 °F +212 °F)</li> <li><b>Water based hydraulic fluids</b> -40 °C +70 °C (-40 °F +158 °F)</li> <li><b>Water and air</b> 0 °C +70 °C (32 °F +158 °F)</li> </ul>	<ul style="list-style-type: none"> <li><b>API 16-D</b></li> <li><b>Alfagomma proprietary hose</b></li> </ul>	
<b>// ALFABIOTECH</b>			
 <b>// ALFABIOTECH 3000 - MT</b> Very high performance in pressure, pulsing and flexing. Four/six high tensile steel spirals. Isobaric hose. Minetuff cover.	<ul style="list-style-type: none"> <li><b>Petroleum based</b> -40 °C +100 °C (-40 °F +212 °F)</li> <li><b>Water based hydraulic fluids</b> -40 °C +70 °C (-40 °F +158 °F)</li> <li><b>Water and air</b> 0 °C +70 °C (32 °F +158 °F)</li> </ul>	<ul style="list-style-type: none"> <li><b>ISO 18752</b></li> <li><b>exceeds SAE R12</b></li> <li><b>Alfagomma proprietary hose</b></li> </ul>	    
 <b>// ALFABIOTECH 4000 - MT</b> Very high performance in pressure, pulsing and flexing. Four high tensile steel spirals. Isobaric hose. Minetuff cover.	<ul style="list-style-type: none"> <li><b>Petroleum based</b> -40 °C +100 °C (-40 °F +212 °F)</li> <li><b>Water based hydraulic fluids</b> -40 °C +70 °C (-40 °F +158 °F)</li> <li><b>Water and air</b> 0 °C +70 °C (32 °F +158 °F)</li> </ul>	<ul style="list-style-type: none"> <li><b>ISO 18752</b></li> <li><b>MED 2014/90/EU</b></li> <li><b>SAE J1942</b></li> </ul>	    
 <b>// ALFABIOTECH 5000 - MT</b> Very high performance in pressure, pulsing and flexing. Four/six high tensile steel spirals. Isobaric hose. Minetuff cover.	<ul style="list-style-type: none"> <li><b>Petroleum based</b> -40 °C +100 °C (-40 °F +212 °F)</li> <li><b>Water based hydraulic fluids</b> -40 °C +70 °C (-40 °F +158 °F)</li> <li><b>Water and air</b> 0 °C +70 °C (32 °F +158 °F)</li> </ul>	<ul style="list-style-type: none"> <li><b>ISO 18752</b></li> <li><b>MED 2014/90/EU</b></li> <li><b>SAE J1942</b></li> </ul>	    

DESCRIPTION	APPLICATION & FLUID COMPATIBILITY	STANDARDS & REGULATIONS	APPROVALS & CERTIFICATES
 <b>// ALFABIOTECH 5000 PLUS - MT</b> Very high performance in pressure, pulsing and flexing. Four high tensile steel spirals. Isobaric hose. Minetuff cover.	<ul style="list-style-type: none"> <li><b>Petroleum based</b> -40 °C +100 °C (-40 °F +212 °F)</li> <li><b>Water based hydraulic fluids</b> -40 °C +70 °C (-40 °F +158 °F)</li> <li><b>Water and air</b> 0 °C +70 °C (32 °F +158 °F)</li> </ul>	<ul style="list-style-type: none"> <li>ISO 18752</li> <li>MED 2014/90/EU</li> <li>SAE J1942</li> </ul>	        
 <b>// ALFABIOTECH 6000 - MT</b> Very high performance in pressure, pulsing and flexing. Four/six high tensile steel spirals. Isobaric hose. Minetuff cover.	<ul style="list-style-type: none"> <li><b>Petroleum based</b> -40 °C +100 °C (-40 °F +212 °F)</li> <li><b>Water based hydraulic fluids</b> -40 °C +70 °C (-40 °F +158 °F)</li> <li><b>Water and air</b> 0 °C +70 °C (32 °F +158 °F)</li> </ul>	<ul style="list-style-type: none"> <li>ISO 18752</li> <li>exceeds SAE R15</li> <li>MED 2014/90/EU</li> <li>SAE J1942</li> </ul>	        
 <b>// ALFABIOTECH EVOLUTION 3000 - MT</b> Very high performance in pressure, pulsing and flexing. Improved bend radius. Four high tensile steel spirals. Isobaric hose. Minetuff cover.	<ul style="list-style-type: none"> <li><b>Petroleum based</b> -40 °C +100 °C (-40 °F +212 °F)</li> <li><b>Water based hydraulic fluids</b> -40 °C +70 °C (-40 °F +158 °F)</li> <li><b>Water and air</b> 0 °C +70 °C (32 °F +158 °F)</li> </ul>	<ul style="list-style-type: none"> <li>ISO 18752</li> <li>exceeds SAE R12</li> <li>Alfagomma proprietary hose</li> <li>SAE J1942</li> </ul>	 
 <b>// ALFABIOTECH EVOLUTION 4000 - MT</b> Very high performance in pressure, pulsing and flexing. Improved bend radius. Four high tensile steel spirals. Isobaric hose. Minetuff cover.	<ul style="list-style-type: none"> <li><b>Petroleum based</b> -40 °C +100 °C (-40 °F +212 °F)</li> <li><b>Water based hydraulic fluids</b> -40 °C +70 °C (-40 °F +158 °F)</li> <li><b>Water and air</b> 0 °C +70 °C (32 °F +158 °F)</li> </ul>	<ul style="list-style-type: none"> <li>ISO 18752</li> <li>MED 2014/90/EU</li> <li>SAE J1942</li> </ul>	 
 <b>// ALFABIOTECH EVOLUTION 5000 - MT</b> Very high performance in pressure, pulsing and flexing. Improved bend radius. Four/six high tensile steel spirals. Isobaric hose. Minetuff cover.	<ul style="list-style-type: none"> <li><b>Petroleum based</b> -40 °C +100 °C (-40 °F +212 °F)</li> <li><b>Water based hydraulic fluids</b> -40 °C +70 °C (-40 °F +158 °F)</li> <li><b>Water and air</b> 0 °C +70 °C (32 °F +158 °F)</li> </ul>	<ul style="list-style-type: none"> <li>ISO 18752</li> <li>MED 2014/90/EU</li> <li>SAE J1942</li> </ul>	 

DESCRIPTION	APPLICATION & FLUID COMPATIBILITY	STANDARDS & REGULATIONS	APPROVALS & CERTIFICATES
 <p><b>// ALFABIOTECH EVOLUTION 5000 PLUS - MT</b> Very high performance in pressure, pulsing and flexing. Improved bend radius. Four high tensile steel spirals. Isobaric hose. Minetuff cover.</p>	<ul style="list-style-type: none"> <li><b>Petroleum based</b> -40 °C +100 °C (-40 °F +212 °F)</li> <li><b>Water based hydraulic fluids</b> -40 °C +70 °C (-40 °F +158 °F)</li> <li><b>Water and air</b> 0 °C +70 °C (32 °F +158 °F)</li> </ul>	<ul style="list-style-type: none"> <li>ISO 18752</li> <li>MED 2014/90/EU</li> <li>SAE J1942</li> </ul>	 
 <p><b>// ALFABIOTECH EVOLUTION 6000 - MT</b> Very high performance in pressure, pulsing and flexing. Improved bend radius. Four/six high tensile steel spirals. Isobaric hose. Minetuff cover.</p>	<ul style="list-style-type: none"> <li><b>Petroleum based</b> -40 °C +100 °C (-40 °F +212 °F)</li> <li><b>Water based hydraulic fluids</b> -40 °C +70 °C (-40 °F +158 °F)</li> <li><b>Water and air</b> 0 °C +70 °C (32 °F +158 °F)</li> </ul>	<ul style="list-style-type: none"> <li>ISO 18752</li> <li>exceeds SAE R15</li> <li>MED 2014/90/EU</li> <li>SAE J1942</li> </ul>	 

## // SUPERTUFF

 <p><b>// ALFABIOTECH 5000 - ST</b> Very high performance in pressure, pulsing and flexing. Four high tensile steel spirals. Isobaric hose. Supertuff cover for excellent abrasion resistance.</p>	<ul style="list-style-type: none"> <li><b>Petroleum based</b> -40 °C +100 °C (-40 °F +212 °F)</li> <li><b>Water based hydraulic fluids</b> -40 °C +70 °C (-40 °F +158 °F)</li> <li><b>Water and air</b> 0 °C +70 °C (32 °F +158 °F)</li> </ul>	<ul style="list-style-type: none"> <li>SAE J1942</li> </ul>	  
 <p><b>// ALFABIOTECH 6000 - ST</b> Very high performance in pressure, pulsing and flexing. Four/six high tensile steel spirals. Isobaric hose. Supertuff cover for excellent abrasion resistance.</p>	<ul style="list-style-type: none"> <li><b>Petroleum based</b> -40 °C +100 °C (-40 °F +212 °F)</li> <li><b>Water based hydraulic fluids</b> -40 °C +70 °C (-40 °F +158 °F)</li> <li><b>Water and air</b> 0 °C +70 °C (32 °F +158 °F)</li> </ul>	<ul style="list-style-type: none"> <li>ISO 18752</li> <li>exceeds SAE R15</li> <li>MED 2014/90/EU</li> <li>SAE J1942</li> </ul>	  
			
			  
			

DESCRIPTION	APPLICATION & FLUID COMPATIBILITY	STANDARDS & REGULATIONS	APPROVALS & CERTIFICATES
-------------	-----------------------------------	-------------------------	--------------------------

## // HIGH TEMPERATURE

 <p><b>// R5 EVOLUTION HT 150</b> Medium pressure hydraulic lines. Specially designed for high temperature applications. One high tensile steel braid.</p>	<ul style="list-style-type: none"> <li>• <b>Hydraulic lines</b> -40 °C +150 °C (-40 °F +302 °F)</li> <li>• <b>Fuel oil</b></li> <li>• <b>Antifreeze solutions</b></li> <li>• <b>Air and water systems</b></li> </ul>	<ul style="list-style-type: none"> <li>• <b>SAE R5</b></li> </ul>	
 <p><b>// 1SN EVOLUTION HT 150</b> High pressure hydraulic lines. Specially designed for high temperature applications. One high tensile steel braid. Not recommended for steam service.</p>	<ul style="list-style-type: none"> <li>• <b>Hydraulic lines</b> -40 °C +150 °C (-40 °F +302 °F)</li> <li>• <b>Fuel oil</b></li> <li>• <b>Antifreeze solutions</b></li> <li>• <b>Air and water systems</b></li> </ul>	<ul style="list-style-type: none"> <li>• <b>SAE 100 R1AT</b></li> <li>• <b>EN 853 1SN</b></li> <li>• <b>ISO 1436-1</b></li> <li>• <b>MED 2014/90/EU</b></li> <li>• <b>Alfagomma proprietary hose</b></li> </ul>	 in progress    

## // OIL RETURN LINES

 <p><b>// FLEXOR R4</b> Suction and delivery. Textile reinforced with embedded steel helix wires.</p>	<ul style="list-style-type: none"> <li>• <b>Hydraulic lines</b> -40 °C +100 °C (-40 °F +212 °F)</li> <li>• <b>Fuel oil</b></li> <li>• <b>Antifreeze solutions</b></li> <li>• <b>Air and water</b></li> </ul>	<ul style="list-style-type: none"> <li>• <b>SAE 100 R4</b></li> <li>• <b>Flame resistance: MSHA</b></li> </ul>	
--	--	--	---

## // INDUSTRIAL HOSE

PETROCHEMICAL			
 <p><b>// 605AA</b> Fuel-oil S&amp;D 10 bar (150 psi) Safety factor: 3:1 ID range: 19 - 203 mm (3/4 - 8") Temp. range: -30 +80 °C (-22 +176 °F)</p>	<ul style="list-style-type: none"> <li>• <b>Fuels</b> max 50% aromatic content</li> <li>• <b>Oils</b></li> <li>• <b>Bilge water</b></li> <li>• <b>Fresh water</b></li> <li>• <b>Sea water</b></li> </ul>	<ul style="list-style-type: none"> <li>• <b>exceed SAE 100R4</b></li> <li>• <b>SAE J2006 Style R2</b></li> <li>• <b>ISO 13363 Type 2 Class B</b></li> <li>• <b>Flame resistance: MSHA</b></li> </ul>	

DESCRIPTION	APPLICATION & FLUID COMPATIBILITY	STANDARDS & REGULATIONS	APPROVALS & CERTIFICATES
 <b>// 658AA</b> <b>Measured fuel dispensing systems</b> <b>16 bar (240 psi)</b> Safety factor: 3:1 ID range: 25 - 51 mm (1 - 2") Temp. range: -30 +55 °C (-22 +131 °F)	<ul style="list-style-type: none"> <li>• <b>Fuels</b> max 50% aromatic content</li> <li>• <b>Oxygenated fuels</b> max 15%</li> <li>• <b>Oils</b></li> <li>• <b>Bilge water</b></li> <li>• <b>Fresh water</b></li> <li>• <b>Sea water</b></li> </ul>	<ul style="list-style-type: none"> <li>• EN 1360 Type 1 Grade Ω</li> <li>• Flame resistance: according to reference standard</li> </ul>	
 <b>// 619AA</b> <b>Fuel-oil S&amp;D</b> <b>16 bar (240 psi)</b> Safety factor: 4:1 ID range: 19 - 102 mm (3/4 - 4") Temp. range: -30 +70 °C (-22 +158 °F)	<ul style="list-style-type: none"> <li>• <b>Fuels</b> max 50% aromatic content</li> <li>• <b>Oxygenated fuels</b> max 15%</li> <li>• <b>Oils</b></li> <li>• <b>Bilge water</b></li> <li>• <b>Fresh water</b></li> <li>• <b>Sea water</b></li> </ul>	<ul style="list-style-type: none"> <li>• EN 12115 Type SD Grade Ω/T</li> <li>• exceed EN 1761 Type SD Grade Ω</li> <li>• Flame resistance: according to reference standard</li> </ul>	
 <b>// 65AAA</b> <b>Aviation fuelling</b> <b>10 bar (150 psi)</b> Safety factor: 4:1 ID range: 38 mm (1 1/2") Temp. range: -30 +65 °C (-22 +150 °F)	<ul style="list-style-type: none"> <li>• <b>Aviation fuels</b> max 30% aromatic content</li> </ul>	<ul style="list-style-type: none"> <li>• EI 1529 Grade 1 Type C</li> <li>• Flame resistance: according to reference standard</li> </ul>	
 <b>// 656AA</b> <b>Aviation fuelling</b> <b>20 bar (300 psi)</b> Safety factor: 4:1 ID range: 25 - 102 mm (1 - 4") Temp. range: -30 +65 °C (-22 +150 °F)	<ul style="list-style-type: none"> <li>• <b>Aviation fuels</b> max 30% aromatic content</li> </ul>	<ul style="list-style-type: none"> <li>• ISO 1825 Type C Grade Ω</li> <li>• EI 1529 Grade 2</li> <li>• Flame resistance: NFPA 407</li> </ul>	
 <b>// 611AA</b> <b>Aviation fuelling-defuelling</b> <b>20 bar (300 psi)</b> Safety factor: 4:1 ID range: 25 - 75 mm (1 - 3") Temp. range: -30 +65 °C (-22 +150 °F)	<ul style="list-style-type: none"> <li>• <b>Aviation fuels</b> max 30% aromatic content</li> </ul>	<ul style="list-style-type: none"> <li>• ISO 1825 Type F Grade Ω</li> <li>• Flame resistance: according to reference standard</li> </ul>	

DESCRIPTION	APPLICATION & FLUID COMPATIBILITY	STANDARDS & REGULATIONS	APPROVALS & CERTIFICATES
 <p><b>// 659AA</b> LPG delivery 25 bar (375 psi)  Safety factor: 4:1 ID range: 13 - 51 mm (1/2 - 2") Temp. range: -30 +70 °C (-22 +158 °F)</p>	<ul style="list-style-type: none"> <li>LPG</li> </ul>	<ul style="list-style-type: none"> <li>EN 1762 Type D Grade M</li> <li>Flame resistance: according to reference standard</li> </ul>	

## MARINE

 <p><b>// 654AA BOAT NEW</b> Marine fuel feed - Hard wall  Working pressure: 20 bar (300 psi) Safety factor: 3:1 ID range: 6 - 25 mm (1/4 - 1") Temp. range: -20 +100 °C (-4 +212 °F)</p>	<ul style="list-style-type: none"> <li>Petrol and diesel fuels</li> <li>Oxygenated fuels max 10%</li> </ul>	<ul style="list-style-type: none"> <li>ISO 7840/A1</li> <li>SAE J1527/A1/R1</li> <li>2013/53/EU</li> <li>Flame resistance: according to reference standard</li> </ul>	
 <p><b>// 616AA BOAT NEW</b> Marine fuel fill - Hard wall  Working pressure: 10 bar (150 psi) Safety factor: 3:1 ID range: 19 - 60 mm (3/4 - 2 3/8") Temp. range: -20 +100 °C (-4 +212 °F)</p>	<ul style="list-style-type: none"> <li>Petrol and diesel fuels</li> <li>Oxygenated fuels max 10%</li> </ul>	<ul style="list-style-type: none"> <li>ISO 7840/A1</li> <li>SAE J1527/A1/R2</li> <li>2013/53/EU</li> <li>Flame resistance: according to reference standard</li> </ul>	
 <p><b>// 653AA</b> Marine exhaust - Soft wall  Working pressure: 3 bar (45 psi) Safety factor: 5:1 ID range: 25 - 203 mm (1 - 8") Temp. range: -30 +100 °C (-22 +212 °F)</p>	<ul style="list-style-type: none"> <li>Wet exhaust</li> <li>Bilge water</li> <li>Fuels max 40% aromatic content</li> <li>Oils</li> </ul>	<ul style="list-style-type: none"> <li>SAE J2006 Style R1</li> <li>ISO 13363 Type 1 Class B</li> </ul>	
 <p><b>// 6E1AA</b> Marine exhaust - Hard wall  Working pressure: 3 bar (45 psi) Safety factor: 5:1 ID range: 25 - 203 mm (1" - 8") Temp. range: -30 +100 °C (-22 +212 °F)</p>	<ul style="list-style-type: none"> <li>Wet exhaust</li> <li>Bilge water</li> <li>Fuels max 40% aromatic content</li> <li>Oils</li> </ul>	<ul style="list-style-type: none"> <li>SAE J2006 Style R1</li> <li>ISO 13363 Type 1 Class B</li> </ul>	

DESCRIPTION	APPLICATION & FLUID COMPATIBILITY	STANDARDS & REGULATIONS	APPROVALS & CERTIFICATES
 <b>// 266LL</b> <b>Marine sanitary hose - PVC</b> <b>Working pressure:</b> 8 - 6 bar (120 - 90 psi) <b>Safety factor:</b> 3:1 <b>ID range:</b> 19 - 38 mm (3/4 - 1 1/2") <b>Temp. range:</b> -5 + 60 °C (+23 +140 °F)	<ul style="list-style-type: none"> <li>• Grey-black water</li> </ul>		
 <b>// 202LL</b> <b>Marine sanitary hose 7 bar (100 psi)</b> <b>Safety factor:</b> 3:1 <b>ID range:</b> 19 - 51 mm (3/4 - 2") <b>Temp. range:</b> -30 +80 °C (-22 +176 °F)	<ul style="list-style-type: none"> <li>• Grey-black water</li> </ul>	<ul style="list-style-type: none"> <li>• ISO 8099</li> </ul>	

## OIL & GAS - DOCK

 <b>// 60GAA</b> <b>Fuel-oil S&amp;D 15 bar (225 psi) - Built in fittings</b> <b>Safety factor:</b> 4:1 <b>ID range:</b> 100 - 300 mm (4 - 12") <b>Temp. range:</b> -20 +82 °C (-4 +180 °F)	<ul style="list-style-type: none"> <li>• Petroleum products max 50% aromatic content</li> <li>• Crude oil</li> </ul>	<ul style="list-style-type: none"> <li>• EN 1765 Type S15</li> </ul>	
 <b>// 60JAA</b> <b>LPG S&amp;D 25 bar (375 psi) - Built in fittings</b> <b>Safety factor:</b> 4:1 <b>ID range:</b> 100 - 300 mm (4 - 12") <b>Temp. range:</b> -30 +70 °C (-22 +158 °F)	<ul style="list-style-type: none"> <li>• LPG</li> </ul>	<ul style="list-style-type: none"> <li>• EN 1762 Type SD Grade M</li> </ul>	

DESCRIPTION	APPLICATION & FLUID COMPATIBILITY	STANDARDS & REGULATIONS	APPROVALS & CERTIFICATES
<b>OIL &amp; GAS - RIG SUPPLY</b>			
 <p><b>// 648AA</b> Fuel-liquid mud <b>20 bar (300 psi) - Soft wall</b> Safety factor: 4:1 ID range: 51 -152 mm (2 - 6") Temp. range: -30 + 90 °C (-22 + 194 °F)</p>	<ul style="list-style-type: none"> <li>• Petroleum products max 50% aromatic content</li> <li>• Methanol</li> <li>• Oil based mud</li> <li>• Drill water</li> <li>• Fresh water</li> <li>• Sea water</li> </ul>	<ul style="list-style-type: none"> <li>• Flame resistance: EN 1762 - Annex A</li> </ul>	 ABS Type approved hose assemblies
 <p><b>// 615AA</b> Fuel-liquid mud <b>20 bar (300 psi) - Hard wall</b> Safety factor: 4:1 ID range: 51 - 152 mm (2 - 8") Temp. range: -30 + 90 °C (-22 + 194 °F)</p>	<ul style="list-style-type: none"> <li>• Petroleum products max 50% aromatic content</li> <li>• Methanol</li> <li>• Oil based mud</li> <li>• Drill water</li> <li>• Fresh water</li> <li>• Sea water</li> </ul>	<ul style="list-style-type: none"> <li>• Flame resistance: EN 1762 - Annex A</li> </ul>	 ABS Type approved hose assemblies
 <p><b>// 622AA</b> Fuel-liquid mud <b>40 bar (600 psi) - Hard wall</b> Working pressure: 40 bar (600 psi) - 35 bar (535 psi) depending on ID Safety factor: 4:1 ID range: 76 - 127 mm (3 - 5") Temp. range: -30 + 90 °C (-22 + 194 °F)</p>	<ul style="list-style-type: none"> <li>• Petroleum products max 50% aromatic content</li> <li>• Methanol</li> <li>• Oil based mud</li> <li>• Drill water</li> <li>• Fresh water</li> <li>• Sea water</li> </ul>	<ul style="list-style-type: none"> <li>• Flame resistance: EN 1762 - Annex A</li> </ul>	 ABS Type approved hose assemblies
 <p><b>// 748AA</b> Bulk material <b>20 bar (300 psi) - Soft wall</b> Safety factor: 4:1 ID range: 102 - 127 mm (4 - 5") Temp. range: -30 +80 °C (-22 +176 °F")</p>	<ul style="list-style-type: none"> <li>• Cement</li> <li>• Barite</li> <li>• Mud</li> <li>• Fresh water</li> <li>• Sea water</li> </ul>		 ABS Type approved hose assemblies

DESCRIPTION	APPLICATION & FLUID COMPATIBILITY	STANDARDS & REGULATIONS	APPROVALS & CERTIFICATES
 <b>// 715AA</b> <b>Bulk material</b> <b>20 bar (300 psi) - Hard wall</b> Safety factor: 4:1 ID range: 102 - 127 mm (4 - 5") Temp. range: -30 +80 °C (-22 +176 °F)	<ul style="list-style-type: none"> <li>• Cement</li> <li>• Barite</li> <li>• Mud</li> <li>• Fresh water</li> <li>• Sea water</li> </ul>		 ABS Type approved hose assemblies
 <b>// 448LI</b> <b>Potable water</b> <b>20 bar (300 psi) - Soft wall</b> Safety factor: 4:1 ID range: 51 - 102 mm (2 - 4") Temp. range: -30 +80 °C (-22 +176 °F)	<ul style="list-style-type: none"> <li>• Potable water</li> </ul>		 ABS Type approved hose assemblies
 <b>// 415LI</b> <b>Potable water</b> <b>20 bar (300 psi) - Hard wall</b> Safety factor: 4:1 ID range: 51 - 102 mm (2 - 4") Temp. range: 30 +80 °C (-22 +176 °F)	<ul style="list-style-type: none"> <li>• Potable water</li> </ul>		 ABS Type approved hose assemblies
 <b>// RIGMASTER WATER HD</b> <b>Water S&amp;D</b> <b>20 bar (300 psi) - Heavy Duty</b> Safety factor: 3:1 ID range: 102 mm (4") Temp. range: -30 + 90 °C (-22 + 194 °F)	<ul style="list-style-type: none"> <li>• Fresh water</li> <li>• Sea water</li> <li>• Glycole</li> </ul>		

## OIL & GAS - FIRE FIGHTING

 <b>// 230AH</b> <b>Sea water - 20 bar (300 psi)</b> <b>Fire Resistant 30 minutes 800 °C</b> Safety factor: 4:1 ID range: 32 - 203 mm (1 1/4 - 8") Temp. range: -30 + 100 °C (-22 +212 °F)	<ul style="list-style-type: none"> <li>• Sea water</li> <li>• Petroleum products max 50% aromatic content</li> </ul>	<ul style="list-style-type: none"> <li>• Flame resistance: ISO 15540</li> </ul>	 ABS Type approved hose assemblies
---	--	---	--

DESCRIPTION	APPLICATION & FLUID COMPATIBILITY	STANDARDS & REGULATIONS	APPROVALS & CERTIFICATES
-------------	-----------------------------------	-------------------------	--------------------------

## POTABLE WATER

 <p><b>// 455LE</b> Liquid food delivery 10 bar (150 psi) Safety factor: 3:1 ID range: 13 - 51 mm (1/2 - 2") Temp. range: -30 + 100 °C (-22 +212 °F)</p>	<ul style="list-style-type: none"> <li>Potable water</li> <li>Liquid food</li> </ul>	<ul style="list-style-type: none"> <li>FDA</li> <li>3-A Sanitary Standards</li> <li>D.M. 21/03/73</li> <li>EC 2004/1935</li> <li>EC 2006/2023</li> </ul>	 <p>ø 13 mm RINA Type approved hose assembly according to D.M. 174/2004</p>
 <p><b>// 405LE</b> Liquid food S&amp;D 10 bar (150 psi) Safety factor: 3:1 ID range: 19 - 102 mm (3/4 - 4") Temp. range: -30 + 100 °C (-22 +212 °F)</p>	<ul style="list-style-type: none"> <li>Potable water</li> <li>Liquid food</li> </ul>	<ul style="list-style-type: none"> <li>FDA</li> <li>3-A Sanitary Standards</li> <li>D.M. 21/03/73</li> <li>EC 2004/1935</li> <li>EC 2006/2023</li> </ul>	 <p>ø 19 - 38 mm RINA Type approved hose assembly according to D.M. 174/2004</p>

## MILITARY & DEFENCE

 <p><b>// 6M0AJ</b> Lightweight liquid fuel transfer - Collapsible - Antistatic wire Working pressure: 5 bar (75 psi) Safety factor: 4:1 ID range: 51 mm (2") Temp. range: -30 +80 °C (-22 +176 °F)</p>	<ul style="list-style-type: none"> <li>Kerosene based petroleum fuel</li> <li>Water</li> </ul>	<ul style="list-style-type: none"> <li>MIL-PRF-53064</li> </ul>	
 <p><b>// 6M1AA</b> Liquid fuel transfer - Collapsible - Antistatic wire Working pressure: 9 - 5 bar (125 - 75 psi) depending on ID Safety factor: 4:1 ID range: 38 -76 m (1 1/2 - 3") Temp. range: -30 +80 °C (-22 +176 °F)</p>	<ul style="list-style-type: none"> <li>Kerosene based petroleum fuel</li> <li>Water</li> </ul>	<ul style="list-style-type: none"> <li>MIL-PRF-370 Type A</li> </ul>	

DESCRIPTION	APPLICATION & FLUID COMPATIBILITY	STANDARDS & REGULATIONS	APPROVALS & CERTIFICATES
 <b>// 6M1AJ</b> <b>Liquid fuel transfer - Collapsible - Antistatic wire</b> <b>Working pressure:</b> 7 bar (100 psi) <b>Safety factor:</b> 4:1 <b>ID range:</b> 51 mm (2") <b>Temp. range:</b> -30 +80 °C (-22 +176 °F)	<ul style="list-style-type: none"> <li>• Kerosene based petroleum fuel</li> <li>• Water</li> </ul>	<ul style="list-style-type: none"> <li>• MIL-PRF-370 Type A</li> </ul>	
 <b>// 6A1AA</b> <b>Liquid fuel transfer - Non collapsible - Antistatic wire</b> <b>Working pressure:</b> 5 - 9 bar (75 - 125 psi) depending on ID <b>Safety factor:</b> 4:1 <b>ID range:</b> 38 - 152 mm (1 1/2 - 6") <b>Temp. range:</b> -30 +80 °C (-22 +176 °F)	<ul style="list-style-type: none"> <li>• Kerosene based petroleum fuel</li> <li>• Water</li> </ul>	<ul style="list-style-type: none"> <li>• MIL-PRF-370 Type B</li> </ul>	
 <b>// 6A1AJ</b> <b>Liquid fuel transfer - Non collapsible - Antistatic wire</b> <b>Working pressure:</b> 5 - 9 bar (75 - 125 psi) depending on ID <b>Safety factor:</b> 4:1 <b>ID range:</b> 38 - 102 mm (1 1/2 - 4") <b>Temp. range:</b> -30 +80 °C (-22 +176 °F)	<ul style="list-style-type: none"> <li>• Kerosene based petroleum fuel</li> <li>• Water</li> </ul>	<ul style="list-style-type: none"> <li>• MIL-PRF-370 Type B</li> </ul>	

DESCRIPTION	APPLICATION & FLUID COMPATIBILITY	STANDARDS & REGULATIONS	APPROVALS & CERTIFICATES
 <b>// 6M3AA</b> <b>Fuel handling system - Collapsible - Antistatic wire</b> Working pressure: 10 bar (150 psi) Safety factor: 4:1 ID range: 76 - 152 mm (3 - 6") Temp. range: -30 +80 °C (-22 +176 °F)	<ul style="list-style-type: none"> <li>• Petroleum fuels</li> </ul>	<ul style="list-style-type: none"> <li>• MIL-PRF-11588 Type III</li> <li>• MIL-DTL-22240 Type A</li> </ul>	
 <b>// 6M4AA</b> <b>Liquid petroleum fuels, dispensing - Collapsible</b> Working pressure: 7 bar (100 psi) Safety factor: 4:1 ID range: 51 mm (2") Temp. range: -30 +80 °C (-22 +176 °F)	<ul style="list-style-type: none"> <li>• Automotive gasoline</li> <li>• Aviation gasoline</li> <li>• Jet fuels</li> <li>• Diesel fuels</li> </ul>	<ul style="list-style-type: none"> <li>• MIL-H-82127 (for replacement purpose only)</li> </ul>	
 <b>// 6A3AA</b> <b>Gasoline and jet fuel S&amp;D</b> Working pressure: 7 bar (100 psi) Safety factor: 4:1 ID range: 51 - 76 mm (2 - 3") Temp. range: -30 +80 °C (-22 +176 °F)	<ul style="list-style-type: none"> <li>• Aromatic gasoline</li> <li>• Jet fuels</li> <li>• Demineralized water</li> </ul>	<ul style="list-style-type: none"> <li>• MIL-DTL-27516</li> </ul>	
 <b>// 65AAA</b> <b>Aviation fuelling 10 bar (150 psi)</b> Safety factor: 4:1 ID range: 38 mm (1 1/2") Temp. range: -30 +65 °C (-22 +150 °F)	<ul style="list-style-type: none"> <li>• Petroleum fuels max 30% aromatic content</li> </ul>	<ul style="list-style-type: none"> <li>• EI 1529 Grade 1 Type C</li> <li>• Flame resistance: according to reference standard</li> </ul>	
 <b>// 656AA</b> <b>Aviation fuelling 20 bar (300 psi)</b> Safety factor: 4:1 ID range: 25 - 102 mm (1 - 4") Temp. range: -30 +65 °C (-22 +150 °F)	<ul style="list-style-type: none"> <li>• Petroleum fuels max 30% aromatic content</li> </ul>	<ul style="list-style-type: none"> <li>• ISO 1825 Type C Grade Ω</li> <li>• EI 1529 Grade 2</li> <li>• Flame resistance: NFPA 407</li> </ul>	

DESCRIPTION	APPLICATION & FLUID COMPATIBILITY	STANDARDS & REGULATIONS	APPROVALS & CERTIFICATES
 <b>// 611AA</b> <b>Aviation fuelling-defuelling</b> <b>20 bar (300 psi)</b>  Safety factor: 4:1 ID range: 25 - 75 mm (1 - 3") Temp. range: -30 +65 °C (-22 +150 °F)	<ul style="list-style-type: none"> <li>• <b>Aviation fuels</b> max 30% aromatic content</li> </ul>	<ul style="list-style-type: none"> <li>• ISO 1825 Type F Grade Ω</li> <li>• Flame resistance: according to reference standard</li> </ul>	
 <b>// 456LJ</b> <b>Potable water discharge</b>  Working pressure: 7 bar (100 psi) Safety factor: 4:1 ID range: 25 - 102 mm (1 - 4") Temp. range: -30 +80 °C (-22 +176 °F)	<ul style="list-style-type: none"> <li>• <b>Potable water</b></li> </ul>	<ul style="list-style-type: none"> <li>• A-A-59567 Grade 3 Class 2</li> </ul>	
 <b>// 406LA</b> <b>Potable water S&amp;D</b>  Working pressure: 5 bar (75 psi) Safety factor: 4:1 ID range: 51 mm (2") Temp. range: -30 +80 °C (-22 +176 °F)	<ul style="list-style-type: none"> <li>• <b>Potable water</b></li> </ul>	<ul style="list-style-type: none"> <li>• A-A-59566 Grade A Style A Class 2</li> </ul>	
 <b>// 406LJ</b> <b>Potable water S&amp;D</b>  Working pressure: 5 bar (75 psi) Safety factor: 4:1 ID range: 51 - 102 mm (2 - 4") Temp. range: -30 +80 °C (-22 +176 °F)	<ul style="list-style-type: none"> <li>• <b>Potable water</b></li> </ul>	<ul style="list-style-type: none"> <li>• A-A-59566 Grade A Style A Class 2</li> </ul>	

## // NOTES



# THE ALFAGOMMA GROUP



## ARGENTINA – Buenos Aires

Moreno Store Center  
Belisario Roldán 2616 - CP. 1744  
La Reja - Bs. As.  
+54 (11) 5365-6062/6063

## AUSTRALIA – Sydney

50 Honeycomb Drive  
Eastern Creek  
Sydney, NSW 2766  
+61 (2) 98 53 09 00  
sydney@alfagomma.com.au

## BELGIUM & NETHERLANDS – Benelux

Koeweideblock 4/D3  
1785 Merchtem  
+32 (052) 509 747  
info.benelux@alfagomma.com

## BRAZIL – Guaranesia

Rua Felice Gennasio 401  
Distrito Indl. Dr. Firmino Rocha de Freitas  
37810-000 - Guaranesia, MG - Brasil  
+55 (35) 35 55 0408  
contato@alfagomma.com.br

## CANADA – Montreal

6550 Abrams  
St. Laurent, Montreal  
Quebec H4S 1Y2  
+1 (514) 33 35 577  
info@alfagomma.ca

## CHINA – Ningbo

No. 296 Taiyuan Road  
Investment Pioneering Centre  
Jiangbei District  
Ningbo, 315022  
+86 (574) 88 15 72 88  
alfagomma.china@alfagomma.com.cn

## FRANCE – Villepinte

Le Sisley – Parc d'activité Paris Nord 2  
23 Allée des Impressionnistes  
93420 Villepinte  
+33 (1) 48172121  
agfrance.info@alfagomma.com

## GERMANY – Herne

Friedrich der Grosse 10  
44628 Herne  
+49 (2323) 14 730  
info.germany@alfagomma.com

## GREECE – Athens

85 Kifissou Avenue  
12241 Aigaleo, Athens  
+30 (210) 41 19 909  
alfagomma-hellas@ath.forthnet.gr

**INDONESIA – Tigaraksa**  
JL. Raya Pemda Tigaraksa km. 4  
No 34, Matagara  
Tigaraksa, Tangerang 15720  
+62 (21) 59 96 301  
jakarta@alfagomma.co.id

**ITALY – Vimercate**  
Via Torri Bianche 1  
20871 Vimercate (MB)  
+39 (039) 60 161  
info@alfagomma.com

**MALAYSIA – Pasir Gudang**  
Plo 405, Jalan Perak 4  
81707 Pasir Gudang  
Negeri Johor Darul Takzim  
+60 (7) 25 72 000  
alfagomma@alfagomma.com.my

**MEXICO – Torreón**  
Av. Industria de la transformacion  
Parque Pymes 585  
27400 Torreón, Coahuila  
+52 8713125026  
alfagomma.mexico@alfagomma.com

**SINGAPORE**  
14 Tuas Ave 11  
Singapore 639080  
+65 6360 9000  
alfagomma@alfagomma.com.sg

**SOUTH AFRICA – Johannesburg**  
17 Quark Crescent Linbro Business Park  
Sandton 2065  
+27 (11) 20 10 900  
alfagomma@alfagomma.co.za

**SOUTH KOREA – Hwasung**  
15 Julteo Gil  
Yangkam-Myun, Hwasung-Si  
Kyungki-Do 18630  
+82 (31) 35 28 671  
alfagomma@alfagomma.co.kr

**UNITED KINGDOM – Haydock**  
43 Wilcock Road  
Old Boston Trading Estate Haydock  
St. Helens WA11 9TG  
+44 (1942) 40 76 80  
haydock.sales@alfagomma.com

**UNITED STATES OF AMERICA – Burlington**  
3520 West Avenue  
IA 52601 Burlington  
+1 (319) 75 89 224  
info@alfagomma.us



**DENMARK – Copenhagen**  
Vallensbaekvej 24,  
2605 Brøndby Copenhagen  
+45 (43) 240400  
info@dunlophiflex.dk

**ESTONIA – Tallin**  
Läike tee 32/1 - Peetri alevik,  
Rae vald - 75312 Harjumaa (Tallinn)  
Tel: +372 (0) 605 4900  
tallinn@dunlophiflex.ee

**FINLAND – Pirkkala**  
Jasperintie 320  
33960 Pirkkala  
+358 (207) 625 700  
info@dunlophiflex.fi

**NETHERLANDS – Deventer**  
Hunneperkade 86  
7418 BT Deventer  
+31 (570) 66 05 70  
info@dunlophiflex.nl

**NORWAY – Oslo**  
Stansveien 27  
Pb. 174 Kalbakken  
0903 Oslo  
+47 (23) 33 86 00  
post@dunlophiflex.no

**SWEDEN – Halmstad**  
Kistinge Industriomrade  
Seldonsvagen 2  
30180 Halmstad  
+46 (104) 14 44 04  
halmstad@dunlophiflex.se



**GERMANY – Ettlingen**  
Pforzheimer Str. 126  
76275 Ettlingen  
+49 (7243) 50 550  
info@argus-fluidtechnik.de

**UNITED KINGDOM – Salisbury**  
Telford Road  
Salisbury, Wiltshire SP2 7PH  
+44 (1722) 42 05 90  
sales@hiflex-europe.com



## HEADQUARTER

Alfagomma SpA  
Via Torri Bianche 1  
20871 Vimercate (MB) Italy  
marketing@alfagomma.com  
www.alfagomma.com